

RMO-010U ISM Band Data receiver For Remote Controller Application

make easy of wireless solution

Yoyang Inc. reserves the right to change the product described in this datasheet. All information contained in this datasheet is subject to change without prior notice. Yoyang Inc. assumes no responsibility for the use of any circuits shown in this datasheet.

ISM band ASK / OOK receiver Module

The RMO-010U ISM band data receiver is an ideal design module used for Car Security System, Home Security System, and Remote controller, etc.

Main Function

- Complete with L/C Filter design
- Frequency Band: 315/434MHz
- Any 2 Lever formats
- Data rate from 300bps to 4Kbps.
- High sensitivity up to -103 dbm
- Low power consume
- Wide operate temperature from -20 $^\circ\!\mathrm{C}~$ -- +70 $^\circ\!\mathrm{C}~$
- Small size
- Low cost

Specification

Module size 44 X12 X 7mm

Description	Part No: RMF-600U	
Frequency stability	30ppm at 25℃	
Operation frequency	315MHz, 434MHz.	
Data Rate	300bps to 4Kbps.	
Modulation	ASK and OOK	
Channel spacing	200Khz.	
Sensitivity	-103dBm at 434MHz by 1200bps	
Working Voltage	DC 5V ± 20%	
Power consumption	4mA	
Working temperature range	-20 to +70℃	
Module Size	44mm X 12mm X 7mm.	
Weight	3 grams.	



Page 1




RMO-010U ISM Band Data receiver For Remote Controller Application

Pin Description

Pin Number	Name	Description
1	GND	Ground
2	Date	Received data output
3	Data	Same with Pin#2
4	VCC	Power supply DC + 5V
5	VCC	Same with Pin #4
6	GND	Ground
7	GND	Ground
8	ANT	Antenna Input

Pin Lead size: 2.54mm 8 pin single

PCB Size and Pin Assignment



Application note for the wire length of antenna

315MHz	433.92MHz
$\lambda = 95$ CM	λ = 70CM
½λ = 47.5CM	½ λ = 47.5CM
$1/4\lambda = 23$ CM	¼λ = 17.5CM
$1/2.1/4\lambda = 12CM$	½.¼λ = 8.75CM

Page 2