TECHNICAL SPRAYS



Weicon Sealant and Adhesive Remover Spray



Weicon Sealant and Adhesive Remover is a fast acting spray that effectively dissolves and eliminates sealants and hardened adhesive residues as well as lacquers and paints. This spray can be used on metal, wood, glass, ceramic, polyethylene and polypropylene and, thanks to its fast acting nature, can even be used on vertical surfaces.

Weicon Sealant and Adhesive Remover is typically used for dissolving sealant residues from cylinder heads, oil pans, water pumps, exhaust manifolds, valve covers and gear flanges and is also used for removing carbon residues, paints and lacquers. It is also used as a paint remover in wood restoration work and for removing all kinds of hardened adhesives including cyanoacrylate and anaerobically hardened adhesives.

Properties

Colour	Colourless
Odour	Mineral Oil
Temperature Resistance	
Minimum Shelf Life	24 Months

Preparation of the Surface

No special surface pre-treatment is required.

Processing

Spray a sufficient quantity of Sealant and Adhesive Remover onto the part/surface and allow time for it to react. If necessary, wipe off with a clean, dry cloth. Repeat process as required.

Sealant and Adhesive Remover Spray should not be used on sensitive plastics such as PVC, synthetics or linoleum.

Storage

Cans of Weicon Sealant and Adhesive Remover Spray should be stored away from direct sunlight and not exposed to temperatures exceeding 50°C. Minimum shelf life is 24 months.

Availability

Weicon Sealant and Adhesive Remover Spray is available in 400ml aerosol cans.

Visit: www.agaus.com.au

Phone: 1300 098 060

Important

This information should not be treated as a substitute for specific technical advice. AG does not offer such advice and cannot warrant the performance or suitability of products for particular applications.

Rev: Jun. 2013 V001457 0000R00715AGDOCg