

MS8261
MS8264
MS8269

DIGITAL MULTIMETERS



MS8261 MS8264 MS8269



- Conform to the IEC1010-1 standard CAT III 600V CAT II 1000V
- Full over load protection
- Resistance fuse inside
- Data hold
- Function characters indication
- Low battery indication
- Auto power off
- Display: 1999 counts
- Weight: Approx . 380g (including battery)
- Size: 195mm x 92mm x 55mm

Specifications		Accuracy		
Function	Range	MS8261	MS8264	MS8269
DC VOLTAGE:	200m/2V /20 V/200 V /1000V	±0.5%	±0.5%	±0.5%
AC VOLTAGE:	200m/2V /20 V/200 V/750V	±0.8%	±0.8%	±0.8%
DC CURRENT:	2mA	±0.8%		
	20mA /200mA	±1.0%	±1.0%	±1.0%
	10A	±2.0%	±2.0%	±2.0%
AC CURRENT:	2mA /200mA	±1.0%	±1.0%	±1.0%
	10A	±3.0%	±3.0%	±3.0%
RESISTANCE:	200/2K/20K/200K/2MΩ/20MΩ	±0.8%	±0.8%	±0.8%
	200MΩ	±5.0%	±5.0%	±5.0%
CAPACITANCE:	2n/20n/200n/2μ/20uF	±4.0%	±4.0%	
	20n/200n/2μ/200uF			±4.0%
INDUCTANCE:	20mH/200mH/2H/20H			±3.0%
FREQUENCY:	20KHz	±1.5%		

Feature	MS8261	MS8264	MS8269
Back light:	✓	✓	
Diode test:	✓	✓	✓
hFE test:	✓	✓	✓
Continuity checking with buzzer:	✓	✓	✓
Temperature:		✓	✓
Power:	9V (6FF22)		

